



<b>PTZ18X50R</b>	
<b>Camera</b>	
Image Sensor	1/2.9" Sony Low Illumination 2.1MP CMOS Sensor
Horizontal Resolution	1080P
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	45°/S
Horizontal Rotation Range	360°
Tilt Rotation Speed	30°/S
Tilt Rotation Range	93°
Auto Flip	Support
Ratio Speed	Support
360° Scan	Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
<b>Night Vision</b>	
Infrared LED	42x6PCS
IR Range	60m
Auto Control IR LED	PWM
<b>Network</b>	
Network protocol	TCP/IP , TTP , NTP , IGMP , DHCP , UDP , SMTP , RTP , RTSP , ARP , DDNS , DNS , PPPoE , P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
<b>General</b>	
Weatherproof	IP66



Operating Temperature	Indoor: 0°~ +40° Outdoor: -20°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	29.5x28x17(cm)
Weight	4.2Kgs